

## RS1AF THRU RS1MF Fast Recovery Rectifier Diodes

### Features

- $I_{F(AV)}$  1A
- $V_{RRM}$  50V-1000V
- High surge current capability
- Polarity: Color band denotes cathode


### Applications

- Rectifier

### Marking

- RS1X

X : From A To M



### Limiting Values(Absolute Maximum Rating)

| Item                                             | Symbol         | Unit             | Test Conditions                                                | RS1        |     |     |     |     |     |      |
|--------------------------------------------------|----------------|------------------|----------------------------------------------------------------|------------|-----|-----|-----|-----|-----|------|
|                                                  |                |                  |                                                                | AF         | BF  | DF  | GF  | JF  | KF  | MF   |
| Repetitive Peak Reverse Voltage                  | $V_{RRM}$      | V                |                                                                | 50         | 100 | 200 | 400 | 600 | 800 | 1000 |
| Maximum RMS Voltage                              | $V_{RMS}$      | V                |                                                                | 35         | 70  | 140 | 280 | 420 | 560 | 700  |
| Average Forward Current                          | $I_{F(AV)}$    | A                | 60Hz Half-sine wave, Resistance load, $T_a = 90^\circ\text{C}$ | 1.0        |     |     |     |     |     |      |
| Surge(Non-repetitive)Forward Current             | $I_{FSM}$      | A                | 60Hz Half-sine wave, 1 cycle, $T_a = 25^\circ\text{C}$         | 30         |     |     |     |     |     |      |
| Operation Junction and Storage Temperature Range | $T_J, T_{STG}$ | $^\circ\text{C}$ |                                                                | -55 ~ +150 |     |     |     |     |     |      |

### Electrical Characteristics (T=25°C Unless otherwise specified)

| Item                          | Symbol               | Unit | Test Condition                                                   |                     | RS1 |    |    |     |    |     |    |
|-------------------------------|----------------------|------|------------------------------------------------------------------|---------------------|-----|----|----|-----|----|-----|----|
|                               |                      |      |                                                                  |                     | AF  | BF | DF | GF  | JF | KF  | MF |
| Peak Forward Voltage          | V <sub>F</sub>       | V    | I <sub>F</sub> =1.0A                                             |                     | 1.3 |    |    |     |    |     |    |
| Maximum reverse recovery time | t <sub>rr</sub>      | ns   | I <sub>F</sub> =0.5A,I <sub>R</sub> =1.0A,I <sub>rr</sub> =0.25A |                     | 150 |    |    | 250 |    | 500 |    |
| Peak Reverse Current          | I <sub>RRM1</sub>    | μA   | V <sub>RM</sub> =V <sub>RRM</sub>                                | T <sub>a</sub> =25℃ | 5   |    |    |     |    |     |    |
|                               | T <sub>a</sub> =125℃ |      |                                                                  | 50                  |     |    |    |     |    |     |    |
| Thermal Resistance(Typical)   | R <sub>θJ-A</sub>    | ℃/W  | Between junction and ambient                                     |                     | 55  |    |    |     |    |     |    |
|                               | R <sub>θJ-L</sub>    |      | Between junction and terminal                                    |                     | 25  |    |    |     |    |     |    |

### Notes:

Thermal resistance from junction to ambient and from junction to lead mounted on P.C.B. with 0.2" x 0.2" (5.0 mm x 5.0 mm) copper pad areas

## Typical Characteristics

FIG.1: FORWARD CURRENT DERATING CURVE




FIG.2: MAXIMUM NON-REPETITIVE FORWARD URGE CURRENT




FIG.3: TYPICAL FORWARD CHARACTERISTICS




FIG.4: TYPICAL REVERSE CHARACTERISTICS






FIG.5: Diagram of circuit and Testing wave form of reverse recovery time




## SMAF Package Outline Dimensions



Dimensions in inches and (millimeters)

## SMAF Suggested Pad Layout



### Note:

1. Controlling dimension: in millimeters.
2. General tolerance:  $\pm 0.05\text{mm}$ .
3. The pad layout is for reference purposes only.